



MATERIAL MILD STEEL S235JR															
FLANGES DIN 2573 PN6				MOD		DESCRIPTION		DRAWN		DATE					
COATING SILICONE PAINT - THERMORESISTANT UP TO 600C, SILVER						Axces B.V. Ondernemersweg 12 4691 SL Tholen The Netherlands www.axces.com +31 (0) 166 603 285		<small>ALL RIGHTS RESERVED THIS DRAWING SHALL NOT BE REPRODUCED WITHOUT THE PRIOR PERMISSION OF AXCES B.V.</small>		<small>NUMBER OF SHEETS</small> 1		<small>DATE</small> 2013-11-12			
WELDING QUALITY ACC. TO 5817 CLASS C								<small>ARTICLE NUMBER</small> 121100000030		<small>DRAWN</small> ES		<small>DAMPING</small> 24 db(A)		<small>SCALE</small> 1 / 4	
TOLERANCES ACC. TO EN-ISO 13920 CLASS B,F				<small>TITLE</small> EXHAUST SPARK ARRESTOR		<small>DRAWING NUMBER</small> 181113/CP24/3		<small>DRAWN</small> ES		<small>DAMPING</small> 24 db(A)		<small>SCALE</small> 1 / 4		<small>FORMAT</small> A3	
DIMENSIONS		LENGTH		ANGLE		STRAIGHTNESS FLATNESS PARALLELSM		<small>TITLE</small> EXHAUST SPARK ARRESTOR		<small>DRAWING NUMBER</small> 181113/CP24/3		<small>DRAWN</small> ES		<small>DAMPING</small> 24 db(A)	
400 mm		+/-2 mm		+/-45'		+/-1,5 mm		<small>TYPE</small> CP24-3" (NB80)		<small>SPARK ARRESTOR</small> BUILT-IN		<small>DRAWN</small> ES		<small>DAMPING</small> 24 db(A)	
1000 mm		+/-3 mm		+/-30'		+/-3 mm		<small>PROJECTION</small> 		<small>WEIGHT</small> 29 Kg		<small>SCALE</small> 1 / 4		<small>FORMAT</small> A3	
2000 mm		+/-4 mm		+/-20'		+/-4,5 mm									
4000 mm		+/-6 mm		+/-20'		+/-6 mm									
>4000 mm		+/-8 mm		+/-20'		+/-8 mm									