



MATERIAL MILD STEEL S235JR									
FLANGES DIN 2573 PN6				MOD	DESCRIPTION			DRAWN	DATE
COATING SILICONE PAINT - THERMORESISTANT UP TO 600C, SILVER						Axces B.V. Ondernemersweg 12 4691 SL Tholen The Netherlands www.axces.com +31 (0) 166 603 285		<small>ALL RIGHTS RESERVED THIS DRAWING SHALL NOT BE REPRODUCED WITHOUT THE PRIOR PERMISSION OF AXCES B.V.</small>	
WELDING QUALITY ACC. TO 5817 CLASS C								<small>NUMBER OF SHEETS</small> 1	<small>DATE</small> 2013-11-12
TOLERANCES ACC. TO EN-ISO 13920 CLASS B,F								<small>ARTICLE NUMBER</small> 121100000050	
DIMENSIONS		LENGTH	ANGLE	STRAIGHTNESS FLATNESS PARALLELSM	TITLE	DRAWING NUMBER	DRAWN		
400 mm		+/-2 mm	+/-45'	+/-1,5 mm	EXHAUST SPARK ARRESTOR	181113/CP24/5	ES		
1000 mm		+/-3 mm	+/-30'	+/-3 mm	TYPE	SPARK ARRESTOR	DAMPING		
2000 mm		+/-4 mm	+/-20'	+/-4,5 mm	CP24-5" (NB125)	BUILT-IN	24 db(A)		
4000 mm		+/-6 mm	+/-20'	+/-6 mm	PROJECTION	WEIGHT	SCALE		FORMAT
>4000 mm		+/-8 mm	+/-20'	+/-8 mm		58 Kg	1 / 6		A3