



MATERIAL MILD STEEL S235JR							
FLANGES DIN 2573 PN 6				MOD	DESCRIPTION	DRAWN	DATE
COATING SILICONE PAINT - THERMORESISTANT UP TO 600C, SILVER					Axces B.V. Ondernemersweg 12 4691 SL Tholen The Netherlands www.axces.com +31 (0) 166 603 285	<small>ALL RIGHTS RESERVED THIS DRAWING SHALL NOT BE REPRODUCED WITHOUT THE PRIOR PERMISSION OF AXCES B.V.</small>	
WELDING QUALITY ACC. TO 5817 CLASS C						<small>NUMBER OF SHEETS</small> 1	<small>DATE</small> 2013-11-05
TOLERANCES ACC. TO EN-ISO 13920 CLASS B,F						<small>ARTICLE NUMBER</small> 111000000040	
DIMENSIONS	LENGTH	ANGLE	STRAIGHTNESS FLATNESS PARALLELSM	TITLE EXHAUST SPARK ARRESTOR	DRAWING NUMBER 181113/SA/4	DRAWN ES	
400 mm	+/-2 mm	+/-45'	+/-1,5 mm	TYPE SA-4" (NB100)	SPARK ARRESTOR BUILT-IN	DAMPING NO	
1000 mm	+/-3 mm	+/-30'	+/-3 mm	PROJECTION 	WEIGHT 15 Kg	SCALE 1 / 3	FORMAT A3
2000 mm	+/-4 mm	+/-20'	+/-4,5 mm				
4000 mm	+/-6 mm	+/-20'	+/-6 mm				
>4000 mm	+/-8 mm	+/-20'	+/-8 mm				